



THE WEIGHT OF THE SASH IS CARRIED
BY THE BEARING
CONNECTED TO THE UPPER FRAME



- **Wide Sash Capability with Top-Mounted Bearings**
The system allows for the use of wide sashes thanks to precision-engineered upper bearings that provide stable and smooth movement.
- **Horizontal Guide Bearings Prevent Rotation**
Special horizontal bearings are positioned to restrict unwanted rotation of the upper bearings, ensuring consistent alignment and safe operation during opening and closing.
- **Sash Load Transferred to the Head Rail via Bearings**
The full weight of the sash is transmitted to the top case and carried by high-capacity bearings, minimizing stress on the threshold and ensuring long-term durability.

Max. sash carrying capacity: 80 kg

TECHNICAL SPECIFICATIONS	
FRAME WIDTH	29 mm
FRAME LENGTH	60 mm
SASH WIDTH	73 mm
SASH LENGTH	60 mm
MAXIMUM SASH CARRYING	80 kg

APPLICATION FEATURES	
UPPER CARRIER BEARINGS	✓
SLOTTED THRESHOLD ALTERNATIVE	✓
POSSIBILITY TO COLLECT THE SASH AT 45°	✓
POSSIBILITY TO COLLECT THE FRAME AT 90°	✓
HEAT AND SOUND INSULATION	✓

